

JUN 12 2006

Appl. No. 10/073,623

Reply to Office Action Dated Mar. 23, 2006

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An image capturing device, comprising:
an electronic image sensor;
a memory including a motion detect routine, a predetermined image interval, and at least one predetermined motion threshold; and

a processor communicating with said electronic image sensor, ~~said a shutter button,~~ and said memory, ~~with said processor being configured to: conducting the capturing of images separated by said predetermined image interval, comparing (a) compare a current a second image to one or more a previous first images, wherein the second image is captured after the first image is captured, determining to determine when if motion between said current second image and said previous first image is below said at least one predetermined motion threshold, and storing (b) store said current second image as a final image if the motion between said second image and said first image is below said at least one predetermined motion threshold, and (c) capture a third image and compare the third image with the second image to determine if motion between said third image and said second image is below said at least one predetermined motion threshold if the motion between said second image and said first image is not below said predetermined motion threshold.~~

2. (Original) The image capturing device of claim 1, said memory further including a predetermined sampling pattern of pixels to be sampled in a captured image and wherein a comparison is performed on pixels included in said predetermined sampling pattern.

3. (Currently Amended) The image capturing device of claim 1, ~~said memory further including a main object specifying a main object in said images and wherein a comparison of~~

Appl. No. 10/073,623
Reply to Office Action Dated Mar. 23, 2006

said main object is performed between said current image and said previous image wherein the processor is configured to compare a main object of the second image with a main object of the first image to determine if motion between said current second image and said previous first image is below said at least one predetermined motion threshold.

4. (Currently Amended) The image capturing device of claim 1, said memory further including a number of regions data dividing a captured image into a plurality of image regions and wherein a region-by-region comparison is performed between said two successive images.

5. (Original) The image capturing device of claim 1, said memory further including a motion detect variable, wherein a motion detection is performed when said motion detect variable is set to an enable state.

6. (Original) The image capturing device of claim 1, wherein said predetermined motion threshold is user-settable.

7. (Original) The image capturing device of claim 1, wherein said processor stores said current image as said final image when said current image is determined to be stable.

8. (Original) The image capturing device of claim 1, wherein said processor stores said current image as said final image when said current image is determined to be stable and a shutter button press is detected.

9. (Original) The image capturing device of claim 1, said memory further including a hold timeout timer that stores a predetermined hold timeout period and wherein said current image is stored as a final image if said hold timeout timer expires.

10. (Original) An image capturing method, comprising the steps of:

BEST AVAILABLE COPY*Appl. No. 10/073,623
Reply to Office Action Dated Mar. 23, 2006*

detecting a shutter button press in order to initiate the image capturing method;
capturing a previous image;
capturing a current image;
comparing said current image and one or more previous images;
determining if said current image is stable with regard to motion; and
converting said current image to be said previous image and repeating the step of
capturing a new image as said current image and repeating the steps of comparing and
determining if said current image is not stable; wherein the step of capturing a current image
and the steps of comparing and determining are repeated until said current image is
determined to be stable.

11. (Original) The method of claim 10, further comprising the step of storing said
current image as a final image when said current image is determined to be stable.

12. (Original) The method of claim 10, further comprising the step of checking a
hold timeout timer and storing said current image as a final image upon expiration of said
hold timeout timer.

13. (Original) The method of claim 10, further comprising the step of waiting a
predetermined image interval between image captures.

14. (Original) The method of claim 10, further comprising the step of storing said
current image as a final image when said current image is determined to be stable.

15. (Original) The method of claim 10, wherein the step of comparing compares all
pixels in said current image and in said previous image.

16. (Original) The method of claim 10, wherein the step of comparing compares a
predetermined sampling pattern of pixels in said current image and in said previous image.

BEST AVAILABLE COPY

BEST AVAILABLE COPY

Appl. No. 10/073,623

Reply to Office Action Dated Mar. 23, 2006

17. (Original) The method of claim 10, wherein the step of comparing compares a predetermined region in said current image and in said previous image.

18. (Original) The method of claim 10, wherein the step of comparing compares a user-designated region in said current image and in said previous image.

19. (Original) The method of claim 10, wherein the step of comparing compares a user-designated object in said current image and in said previous image.

20. (Currently Amended) The method of claim 10, wherein the step of comparing compares a plurality of regions in said current image to a corresponding plurality of regions in said previous image, and wherein said current image is determined to be stable when all regions in said plurality of ~~image~~ regions are determined to be stable.

21. (Currently Amended) An image capturing method, comprising the steps of:
 capturing a ~~previous~~ first image;
 capturing a ~~current~~ second image after capturing the first image;
 comparing said ~~current~~ the second image and one or more previous images to the first
image;
 determining if said ~~current~~ the second image is stable with regard to motion;
~~converting said current image to be said previous image and repeating the step of~~
~~capturing a new image as said current image and repeating the steps of comparing and~~
~~determining if said current image is not stable; and~~
~~detecting a shutter button press when said current image is stable; wherein the step of~~
~~capturing a current image and the steps of comparing and determining are repeated until said~~
~~current image is determined to be stable~~
if the second image is stable with regard to motion, then storing the second image as
a final image, and
if the second image is not stable with regard to motion, then (i) capturing a third
image and (ii) comparing the third image to the second image.

Appl. No. 10/073,623
Reply to Office Action Dated Mar. 23, 2006

BEST AVAILABLE COPY

22. (Currently Amended) The method of claim 21, wherein said ~~current-second~~ image is stored as ~~a~~ the final image when said ~~current-second~~ image is determined to be stable and said ~~a~~ shutter button press is detected.

23. (Currently Amended) The method of claim [[21]] 22, further comprising the step of checking a hold timeout timer while waiting for said ~~a~~ shutter button press ~~and repeating the step of capturing a current image and repeating the comparing and determining steps upon expiration of said hold timeout timer.~~

24. (Currently Amended) The method of claim 21, further comprising the step of waiting a predetermined ~~image-time~~ interval between image captures.

25. (Currently Amended) The method of claim 21, wherein the step of comparing compares all pixels in said ~~current-second~~ image and in said ~~previous-first~~ image.

26. (Currently Amended) The method of claim 21, wherein the step of comparing compares a predetermined sampling pattern of pixels in said ~~current-second~~ image and in said ~~previous-first~~ image.

27. (Currently Amended) The method of claim 21, wherein the step of comparing compares a predetermined region in said ~~current-second~~ image and in said ~~previous-first~~ image.

28. (Currently Amended) The method of claim 21, wherein the step of comparing compares a user-designated region in said ~~current-second~~ image and in said ~~previous-first~~ image.

Appl. No. 10/073,623
Reply to Office Action Dated Mar. 23, 2006

29. (Currently Amended) The method of claim 21, wherein the step of comparing compares a user-designated object in said ~~current~~second image and in said ~~previous~~first image.

30. (Currently Amended) The method of claim 21, wherein the step of comparing compares a plurality of regions in said ~~current~~second image to a corresponding plurality of regions in said ~~previous~~first image, and wherein said ~~current~~second -image is determined to be stable when all regions in said plurality of ~~image~~ regions are determined to be stable.

BEST AVAILABLE COPY